


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H02J 7/00, G09F 9/00, B26B 19/00	A1	(11) International Publication Number: WO 97/22172 (43) International Publication Date: 19 June 1997 (19.06.97)
(21) International Application Number: PCT/IB96/01309 (22) International Filing Date: 27 November 1996 (27.11.96) (30) Priority Data: 95203480.9 14 December 1995 (14.12.95) EP (34) Countries for which the regional or international application was filed: NL et al. (71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventor: LOMHOLT, Ole; Prof. Holstlaan 6, NL-5656 AA (74) Agent: HESSELMANN, Gerardus, J., M.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: CN, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: APPARATUS COMPRISING A RECHARGEABLE BATTERY AND A DISPLAY ON WHICH THE DISPLAY SYMBOLS APPEARING DURING A CYCLE OF USE OF THE BATTERY ARE DISPLAYED IN AN ACCELERATED MANNER IN A DEMONSTRATION MODE		
(57) Abstract An apparatus (1) has a display (D) on which the signs which appear on the display during a cycle of use of the apparatus (1) are displayed in an accelerated manner in a demonstration mode. 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

Apparatus comprising a rechargeable battery and a display on which the display symbols appearing during a cycle of use of the battery are displayed in an accelerated manner in a demonstration mode.

The invention relates to an apparatus comprising: a rechargeable battery for powering inter alia a load in the apparatus, a display with signs for indicating a status of operational functions of the apparatus, and a control system for activating the signs in dependence on a condition of use of the apparatus during a cycle of use of the apparatus, 5 which cycle corresponds to recharging and to discharging of the rechargeable battery.

Such an apparatus, particularly a shaving apparatus, is sold under various type numbers by Philips Electronics. The rechargeable battery of this know shaving apparatus powers a motor which drives the shaving system. Depending on the type of shaving apparatus the display shows inter alia how much charge is left in the battery or to 10 how many minutes of shaving this corresponds. Moreover, signs or symbols are shown to indicate whether the battery is to be charged or when the shaving system is to be cleaned. When such a shaving apparatus is purchased, the salesman will have to revert to the Instructions for Use in order to explain to the prospective buyer how the apparatus operates and what the meaning is of the signs and symbols on the display. Also in a situation in which 15 the user has forgotten how the apparatus works, it will always be necessary to consult the Instructions for Use for an explanation. At such instants of purchasing and subsequently when the operation of the apparatus is to be recollected, the Instructions for Use are generally not available or have been mislaid.

It is an object of the invention to solve this problem. To this end, 20 according to the invention, the apparatus of the type defined in the opening paragraph is characterized in that the control system includes a demonstration mode for a demonstration on the display of a cycle of use of the apparatus by displaying in an accelerated manner the signs in the sequence of their appearance during the cycle of use.

The demonstration mode simulates the cycle of use within a short time, in 25 which all the relevant signs and symbols are shown on the display in chronological sequence. In one or more short demonstrations the salesman can then explain to the prospective buyer what happens and where the signs on the display serve for. Subsequently, the buyer himself can also start the demonstration mode to call to mind the operation of the apparatus and the meaning of the signs and symbols on the display. The demonstration mode is particularly

useful in the case of apparatuses having rechargeable batteries because the correct interpretation of the signs and symbols on the display is of great importance for the user in view of the residual charge in the battery.

The invention can be used not only in shavers but also in other
5 apparatuses having rechargeable batteries, such as depilators, tooth brushes, dental jets, screwdrivers, drills, vacuum cleaners, mixers and the like. In all these apparatuses the demonstration mode in accordance with the invention is very useful. During the demonstration mode the load of the apparatus, for example the motor of a shaving apparatus, can be activated in order to enhance the effect of the demonstration. Moreover, the same
10 acoustic signals may be given as in a normal cycle of use in order to attract attention.

A particularly useful display feature is the display of signals for the indication of the estimated number of usage periods available with the residual charge in the battery. This is particularly important in the case of apparatuses, in particular shavers and the above-mentioned other apparatuses, which are used in accordance with a regular pattern. In
15 the case of a shaver this is for example once a day. The user can then read directly how many shaves are approximately available before the battery is to be recharged. The necessity of recharging can also be indicated by means of a sign on the display.

In the case of a shaving apparatus it is also useful to have an indication that a minor or a major cleaning operation of the shaving system is due by means of signs
20 indicative of a cleaning operation of the shaving system. It may be useful to include this cleaning indication in the demonstration mode, so that the user can see when he is expected to clean the shaving apparatus.

A shaving apparatus with said indications, signs or symbols may be provided with a demonstration mode, which is characterized in that the demonstration mode
25 includes at least one of the following phases:

- a first phase in which all the signs appearing during the cycle of use are displayed at the same time, at option accompanied by the acoustic signalling;
- a second phase in which the sign for indicating the recharging of the battery and the signs for indicating the residual number of usage periods are displayed, the
30 signs for indicating the residual number of usage periods indicating an increasing number of usage periods until a maximum number of usage periods is reached, after which the signs for indicating the residual number of usage periods give an indication that the rechargeable battery is fully charged;
- a third phase in which the signs for indicating the residual number of

usage periods show a number of usage periods which decreases from the maximum number of usage periods to a first intermediate value, optionally with the electric motor running;

- a fourth phase in which a first selection of the signs for indicating a cleaning operation is shown, at option accompanied by the acoustic signalling;
- 5 - a fifth phase in which the signs for indicating the residual number of usage periods show a number of usage periods which decreases from the first intermediate value to a second intermediate value, at option with the electric motor switched on;
- a sixth phase in which a second selection of the signs for indicating a cleaning operation is shown, at option accompanied by the acoustic signalling;
- 10 - a seventh phase in which the signs for indicating the residual number of usage periods show a number of usage periods which decreases from the second intermediate value to a minimum value, at option with the electric motor switched on;
- an eighth phase in which the sign is displayed to indicate recharging of the battery, at option accompanied by the acoustic signalling;
- 15 - a ninth phase in which all the signs appearing during the cycle of use are displayed at the same time.

A further embodiment of this is characterized in that the demonstration mode further comprises: a return to the second phase after completion of the ninth phase and repeating of the second and subsequent phases in a loop. The demonstration then proceeds in
20 an endless loop and is suitable for use at a point of sale or in a presentation.

These and other aspects of the invention will be described and elucidated with reference to the accompanying drawings, in which

Figure 1 shows an electrical block diagram of an apparatus in accordance with the invention;

25 Figure 2 shows an apparatus in accordance with the invention; and

Figure 3 shows a display for use in an apparatus in accordance with the invention.

Figure 1 shows a functional block diagram of an apparatus in accordance with the invention. The apparatus is, for example, a shaving apparatus with rechargeable
30 batteries, but a similar block diagram is applicable to various other rechargeable apparatuses, such as epilators, tooth brushes, dental jets, screwdrivers, drills, vacuum cleaners, mixers and the like. The shaving apparatus has a rechargeable battery B, which is recharged from the mains by means of a power supply PS. The battery B supplies current to a motor MR via a series resistor RS. An electronic switch ES connects the motor MR and the series resistor

RS to the battery B under control of a microcontroller MC, which responds to an on/off switch S. The microcontroller MC applies data to a display D, for example an LCD (Liquid Crystal Display) and activates an acoustic reproducer BP. The microcontroller MC further has a time reference, for example a clock oscillator OSC, from which units of time ΔT are
5 derived. When the electronic switch ES is closed, motor current flows through the series resistor RS, across which a voltage appears which is proportional to the motor current. By means of a voltage-to-frequency converter VFC the voltage across the series resistor RS is converted into a series of pulses whose repetition frequency is proportional to the motor current. The microcontroller counts the number of pulses per unit of time. Each pulse
10 represents a given amount of charge ΔQ flowing from the battery B to the motor MR. For an example of such a voltage-to-current converter reference is made to United States Patent No. 5,144,218. During charging the power supply PS supplies a constant current to the battery B until the battery B is fully charged or until charging is interrupted. The power supply PS and the microcontroller MC communicate with another so as to allow the microcontroller MC to
15 determine how much charge PS has supplied to the battery B by measuring the charging time. The power supply PS can be a commercially available switchable constant current source or the power supply of the afore-mentioned shaving apparatuses.

When the motor MR is running the microcontroller MC computes the charge drain on the basis of the elapsed units of time ΔT and the number of units of charge
20 ΔQ counted during one shave. After a number of shaves, the microcontroller computes the average charge drain per shave and the number of residual shaves still possible with the charge left in the battery B. This number is visible on the display D, so that the user knows approximately how many shaves are still available with the charge in the battery B. The average charge drain per shave is calculated by taking the sum of the individual charge
25 drains of the successive shaves and dividing the sum by the corresponding number of shaves.

The microcontroller MC can also compute the average motor current per shave on the basis of the number of pulses supplied by the voltage-to-frequency converter VFC. From the average motor current and the residual charge in the battery B it is then possible to calculate the shaving time still available. The microcontroller MC then displays
30 the residual shaving time as a number of "minutes left" on the display D.

Another alternative is to indicate the residual charge in the battery B in percent on the display D on the basis of the residual charge left in the battery B. The microcontroller MC then computes the residual charge in the battery B by subtracting the units of charge ΔQ consumed from the instantaneous charge in the battery B.

Figure 2 shows a shaving apparatus having a housing 1 provided with the on/off switch SW and the display D. The housing 1 accommodates the motor MR, which drives the shaving system 2, and the electronic devices shown in the block diagram in Figure 1.

Figure 3 shows the display D of the shaving apparatus. The sign or symbol S1 indicates that the battery B is to be charged. The digits S2A and S2B indicate the residual number of usage periods in combination with the sign S2C, which shows the word "CLEANING". The sign S3 indicates that a major cleaning of the shaving system 2 is due. The digits S4A and S4B indicate that a major cleaning of the shaving system 2 is due. The microcontroller computes when a cleaning of the shaving system 2 is due, and the user performs the cleaning. The sign S5 indicates that the battery B is exhausted except for a charge reserve.

The signs on the display D are displayed at certain instants in a cycle of use of the battery B. The cycle of use is the time interval of the battery B. During the cycle of use the shaving apparatus is utilized, the battery B being discharged. The microcontroller MC can be set to a demonstration mode in which the signs on the display are displayed statically or flashing in the sequence of their appearance in a cycle of use, at option accompanied by sound signals from the acoustic reproducer BP and/or with the motor MR running.

The demonstration mode may comprise, for example, the following phases:

- a first phase in which all the signs S1, S2A, S2B, S2C, S3, S4A, S4B, S4C appearing during the cycle of use are displayed, at option accompanied by the acoustic signalling BP.

The user is thus given an overview of the signs.

- a second phase in which the sign S1 for indicating recharging of the battery B and the signs S2A, S2B for indicating the residual number of usage periods are displayed, the signs for indicating the residual number of usage periods indicating an increasing number of usage periods until a maximum number of usage periods is reached, after which the signs for indicating the residual number of usage periods give an indication that the rechargeable battery is fully charged.

The sign S1 symbolizes recharging of the battery B. The increasing number of usage periods

symbolizing the increasing charge in the battery B. The fully charged condition of the battery B can, for example, be represented by the word "FULL", which is for example displayed as a moving news trailer by means of the characters S2A and S2B.

The second phase consequently symbolizes the charging phase of the battery B.

5

- a third phase in which the signs S2A, S2B for indicating the residual number of usage periods show a number of usage periods which decreases from the maximum number of usage periods to a first intermediate value, optionally with the electric motor MR running.

10 The third phase symbolizes the use of the apparatus, during which the residual number of usage periods decreases.

- a fourth phase in which a first selection S3 of the signs for indicating a cleaning operation is shown, at option accompanied by the acoustic signalling BP.

15 The fourth phase symbolizes the minor cleaning operation which is necessary after a number of shaves.

- a fifth phase in which the signs S2A, S2B for indicating the residual number of usage periods show a number of usage periods which decreases from the first
20 intermediate value to a second intermediate value, at option with the electric motor MR switched on.

The fifth phase is basically similar to the third phase. The usage-period counter is then further decremented.

25 - a sixth phase in which a second selection S3, S4A, S4B, S4C of the signs for indicating a cleaning operation is shown, at option accompanied by the acoustic signalling BP.

The sixth phase symbolizes the major cleaning operation which is necessary after a greater number of shaves.

30

- a seventh phase in which the signs S2A, S2B for indicating the residual number of usage periods show a number of usage periods which decreases from the second intermediate value to a minimum value, at option with the electric motor MR switched on, after which the sign S5 is displayed.

The seventh phase is also basically similar to the third or the fifth phase. The usage-period counter is decremented to zero. The battery B is then exhausted except for the charge reserve, which is indicated by the sign S5 with the word "RESERVE".

- 5 - an eighth phase in which the sign S1 is displayed to indicate recharging of the battery B, at option accompanied by the acoustic signalling BP.
The eighth phase indicates that the battery B is to be recharged.

- a ninth phase in which all the signs S1, S2A, S2B, S2C, S3, S4A, S4B,
10 S4C appearing during the cycle of use are displayed at the same time.
The ninth phase indicates the end of the demonstration.

- If desired, the demonstration mode may return to the second phase after completion of the ninth phase so as to obtain an endlessly repeated demonstration. This option is particularly useful if the power supply PS is connected to the mains voltage because
15 the battery B is then not exhausted by the endless demonstration. The connection to the mains voltage is then detected by the microcontroller MC, which in this case can choose from a single demonstration or a recurrent demonstration. The demonstration mode can be started, for example, by pressing the on/off switch S for a longer time than required for normal operation. If desired, it may be omitted to run the motor MR in the recurrent
20 demonstration mode. Thus, the shaving apparatus can serve as a permanent eyecatcher in a shop without any wear of the apparatus.

- It will be evident that the signs on the display D are related to the function for which the apparatus is used and that in a demonstration mode of an electric tooth brush or a vacuum cleaner having rechargeable batteries other symbols or signs will be
25 displayed in another sequence than in the shaving apparatus described hereinbefore.

CLAIMS:

1. An apparatus comprising: a rechargeable battery (B) for powering inter alia a load (MR) in the apparatus, a display (D) with signs (S1, S2A, S2B, S2C, S3, S4A, S4B, S4C, S5) for indicating a status of operational functions of the apparatus, and a control system (MC) for activating the signs in dependence on a condition of use of the apparatus
5 during a cycle of use of the apparatus, which cycle corresponds to recharging and to discharging of the rechargeable battery (B), characterized in that the control system (MC) includes a demonstration mode for a demonstration on the display (D) of a cycle of use of the apparatus by displaying in an accelerated manner the signs (S1, S2A, S2B, S2C, S3, S4A, S4B, S4C, S5) in the sequence of their appearance during the cycle of use.
- 10 2. An apparatus as claimed in Claim 1, characterized in that the control system (MC) further comprises means (ES) for activating the load (MR) during the demonstration mode.
3. An apparatus as claimed in Claim 1 or 2, characterized in that the apparatus further comprises an acoustic signalling (BP) which can be activated by the control
15 system (MC) inter alia during the demonstration mode.
4. An apparatus as claimed in Claim 1, 2 or 3, characterized in that a number (S2A, S2B, S2C) of the signs on the display (D) give an indication which is related to a residual charge in the rechargeable battery (B).
5. An apparatus as claimed in Claim 4, characterized in that the indication
20 includes signs (S2A, S2B, S2C) for indicating a residual number of usage periods.
6. An apparatus as claimed in Claim 5, characterized in that the apparatus is a shaving apparatus, the load being an electric motor (MR) for driving a shaving system (2).
7. An apparatus as claimed in Claim 6, characterized in that the display (D) further comprises signs (S3, S4A, S4B, S4C) for indicating a cleaning operation of the
25 shaving system (2) and a sign (S1) for indicating recharging of the rechargeable battery (B).
8. An apparatus as claimed in Claim 7, characterized in that the demonstration mode includes at least one of the following phases:
 - a first phase in which all the signs (S1, S2A, S2B, S2C, S3, S4A, S4B, S4C, S5) appearing during the cycle of use are displayed at the same time, at option

accompanied by the acoustic signalling (BP);

- a second phase in which the sign (S1) for indicating the recharging of the battery (B) and the signs (S2A, S2B) for indicating the residual number of usage periods are displayed, the signs for indicating the residual number of usage periods indicating an increasing number of usage periods until a maximum number of usage periods is reached, after which the signs for indicating the residual number of usage periods give an indication that the rechargeable battery is fully charged;
- a third phase in which the signs (S2A, S2B) for indicating the residual number of usage periods show a number of usage periods which decreases from the maximum number of usage periods to a first intermediate value, optionally with the electric motor (MR) running;
- a fourth phase in which a first selection (S3) of the signs for indicating a cleaning operation is shown, at option accompanied by the acoustic signalling (BP);
- a fifth phase in which the signs (S2A, S2B) for indicating the residual number of usage periods show a number of usage periods which decreases from the first intermediate value to a second intermediate value, at option with the electric motor (MR) switched on;
- a sixth phase in which a second selection (S3, S4A, S4B, S4C) of the signs for indicating a cleaning operation is shown, at option accompanied by the acoustic signalling (BP);
- a seventh phase in which the signs (S2A, S2B) for indicating the residual number of usage periods show a number of usage periods which decreases from the second intermediate value to a minimum value, at option with the electric motor (MR) switched on;
- an eighth phase in which the sign (S1) is displayed to indicate recharging of the battery (B), at option accompanied by the acoustic signalling (BP);
- a ninth phase in which all the signs (S1, S2A, S2B, S2C, S3, S4A, S4B, S4C) appearing during the cycle of use are displayed at the same time.

9. An apparatus as claimed in Claim 8, characterized in that the demonstration mode further comprises: a return to the second phase after completion of the ninth phase and repeating of the second and subsequent phases in a loop.

1/2




FIG. 1

2/2




FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 96/01309

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H02J 7/00, G09F 9/00, B26B 19/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: G09F, H02J, B26B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4398834 A (Y.WAKAI), 16 August 1983 (16.08.83), column 1, line 49 - column 2, line 6 --	1-9
X	EP 0417728 A2 (SIEMENS AKTIENGESELLSCHAFT), 20 March 1991 (20.03.91), column 1, line 20 - column 3, line 37 --	1-9
A	EP 0425044 A1 (N.V.PHILIPS'GLOEILAMPENFABRIEKEN), 2 May 1991 (02.05.91), column 5, line 34 - line 57 -- -----	1-9

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

9 April 1997

18 -04- 1997

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Håkan Sandh
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/IB 96/01309

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	4398834	A	16/08/83	CH 647126 A	15/01/85
				GB 2052112 A,B	21/01/81
				JP 55166084 A	24/12/80

EP	0417728	A2	20/03/91	NONE	

EP	0425044	A1	02/05/91	AT 109896 T	15/08/94
				CN 1027192 B	28/12/94
				CN 1051793 A	29/05/91
				DE 69011462 D,T	02/03/95
				JP 3178530 A	02/08/91
				US 5144218 A	01/09/92

THIS PAGE BLANK (USPTO)

Docket # 2TP03P01362

Applic. # 10/590,370

Applicant: Haase

Lerner Greenberg Sterner LLP
Post Office Box 2480
Hollywood, FL 33022-2480
Tel: (954) 925-1100 Fax: (954) 925-1101

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)